

## TECHNICAL DATA SHEET

## **BEGER THINNER #M-59**

Special Thinner for Wood Application (Matt)

	Special Tilliner for Wood Application (Water			
Description	Beger Thinner #M-59 based on blending of aromatic and aliphatic solvents.  Beger Thinner #M-59 is for the dilution of matting solution of one component polyurethane and two components polyurethane and varnish coating to give the optimal performance on the drying time and solubility.			
Properties for Use	* Polyurethane  - Beger Polyurethane B-5000/I-511 90% matt for interior  - Beger Polyurethane B-5000/I-513 70% matt for interior  - Beger Polyurethane B-5000/E-511 clear matt for exterior			
Film Thickness and Spreading Rate	Minimum	Maximum	Typical	
* Dry film thickness (microns)	0	0	0	
* Wet film thickness (microns)	0	0	0	
* Theoretical coverage rate (m/U.S.Gallon/coat)	0	0	0	
Dhysical Duopouties				
Physical Properties	A Nomotio / Alimbetic Column			
* Vehical type	: Aromatic / Aliphatic Solvent			
* Finish	: Matt			
* Colour	: Water Clear			
* Viscosity (@25'C)	.000 000			
* Specific gravity	: 0.90 - 0.98			
* Solid by volume				
* Solid by weight	<del> </del>			
* Dry time (@25'C, 30 mm.DFT)				
Touch dry	<del>   </del> 			
Recoat	<del>  -</del> 			
Dry to handle	Year agree			
* Flash point	: More than 35'C			
Application Method				
* Tool	: Roller, brush and spray gun.			
* Thinner	:-			
* Condition during application	: Application by roller and brush : dilute with 10 - 15% Beger Thinner #M-59 by volume.			
	: Application by spray gun : dilute with 15 - 20% Beger Thinner #M-59 by volume.			
Storage	. Handle with care Stin well before and o	passionally during application		
Storage	<ul> <li>: Handle with care. Stir well before and occasionally during application.</li> <li>: The product must be stored in accordance with national regulations. Storage conditions are to keep the containe in a dry, cool, well ventilated space and away form source of heat an ignition.</li> <li>: Containers must be kept tightly closed.</li> <li>: 12 months at ambient.</li> </ul>		conditions are to keep the containers	
. 12 months at amplent.				
Health and safety	: Use under well ventilated conditions.			
	: Do not breathe or inhale mist.			
	: Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water.			
	: Eyes should be well flushed with water and medical attention sought immediately.			
Precaution	: Keep out of reach of children.			
	- 1100p out of femen of enhancin			
Reference Standard	:-			
Docking Circ	1/4 College 1 Coll			
Packing Size	: 1/4 Gallon, 1 Gallon.			



DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control,

TECHNICAL DATA SHEET
Edition: April 2011

Page : 1 of 1 Beger Thinner #M-59