

Description	Beger Shield Art Effects (Rusty Glow) is may be applied to many different surfaces, for example cement, plaster, plaster of Paris, plasterboard, wood, iron and even surfaces that have already been painted (provided that the existing coat is not peeling. No added lead and no added mercury to ensure for health and environmental safe.		
Feature and Benefits	<ul style="list-style-type: none"> * Excellent adhesion. * Easy washable. * No musty odor. * Excellent efflorescence and alkali resistance. * Free lead and mercury. * Zero VOCs. * Product imported from Italy. 		
Film Thickness and Spreading Rate	Minimum	Maximum	Typical
* Dry film thickness (microns)	0	0	0
* Wet film thickness (microns)	0	0	0
* Theoretical coverage rate (m ² /Litre/Coat)	6	8	Actual consumption rate depends on application method and surface condition.
Physical Properties	<ul style="list-style-type: none"> * Vehicle type : Water-based paint (Special luminescent sandy reflections) * Colour : According to the "Beger Shield Art Effects (Rusty Glow)" * Dry time (@25°C, 30 mm.DFT) : 2 hours Touch dry : - Recoat : 24 hours Dry to handle 		
Application Method	<ul style="list-style-type: none"> * Tool : Brush. * Thinner : Ready to use. * Condition during application : The moisture content in the concrete should not exceed 14%. 		
Application System	<ul style="list-style-type: none"> * Surface preparation : Surface should be dry and clean. : Remove completely all dirt, grease, oil, water or any contaminated by washing surface with suitable cleaner. : Repair all surface imperfections. Before application, fill and seal hairline cracks by working a generous amount of material into void. Cracks and gaps wider than 2.0 - 10.0 mm. should be filled with acrylic sealant. Use Beger Acrylic Wall Filler #F-200 for cracks and gaps with less than 0.3 - 1.0 mm. width. : Surface with fungus, mold and mildew growth must be cleaned off and follow by the treatment of fungicidal wash Beger Mouldfree #M-001. : Previous painted surface: Remove all loose or peeling paint. Remove chalk with high pressure-water jet; allow to dry a minimum of 24 hours. * Typical paint system <ul style="list-style-type: none"> * Primer : Beger Shield Art Effects Primers #1000 1 coat * Top coat : Beger Shield Art Effects (Rusty Glow) 1 coat 		
Storage	<ul style="list-style-type: none"> : Storage at a temperature no lower +1°C and no higher than +30°C. : Containers must be kept tightly closed even after use. 		
Health and safety	: -		
Precautions	: -		
Reference Standard	: -		
Packing Size	: 1 Litre and 3 Litres.		

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control,

We cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice. Beger Shield Art Effects (Rusty Glow)